

Built for a lifetime."

Portable Compressors **Mobilair[™] M15 / M17**



Compact and Reliable

The Mobilair[™] M15 and M17 are rugged and dependable units that are perfect for a variety of applications. Light construction, post driving, carpentry, and monument engraving are just a few jobs where the M15 and M17 are ideal. With a folding handle, oversized pneumatic tires, and compact design, these units are easy to move around virtually any job site.

The M15 and M17 feature Kaeser's power saving Sigma Profile[™] airend. This efficient Kaeser design maintains steady pressure and signature performance to lower your fuel bill by delivering maximum cfm per horsepower. Driving these airends are quiet but powerful Honda engines with modulation control which match air output to load demand. They both have a simple electric starter with keyed ignition and an easy-to-read control panel.

The scratch, dent, and impact resistant rotomolded polyethylene shell takes a beating and still protects the unit. Inside, the compressors are protected by 4 micron inlet filters rated at 99.9% efficiency, allowing these units to operate in virtually any construction environment. **Capacity:** 50 cfm or 60 cfm (operates up to 60 lb. paving breaker)

Pressure: 100 psig

Standard Features:

- Single stage, oil injected rotary screw airend with power-saving, proprietary Sigma Profile
- 4-cycle, V-twin industrial duty Honda engine
- · Engine rated 21 hp
- · Uses lead-free gasoline
- Compressor and engine are disengaged for easy starting, even in cold conditions
- Convenient one-touch electric start
- Belt-driven with a three-groove power band
- Control panel displays pressure and hour meter
- Protective rotomolded polyethylene enclosure
- Vibration isolation for smooth, quiet operation
- 4 micron air intake filters protect the airend

Optional Features:

- Stationary mounting
- Five year airend warranty
- Higher pressures available

kaeser.com

Technical Specifications

COMPRESSOR			GASOLINE ENGINE				PACKAGE			DIMENSIONS
Model	Free Air D 100 psig (cfm)	elivery at 217 psig (cfm)	Make	Power @ Full Load (hp)	Full Load Speed (rpm)	Off Load Running Speed (rpm)	Fuel Tank Capacity (gal)	Weight (lb.)	Outlets	L* x W x H (in.)
M15	50	—	Honda GX630	14.8	3000	2200	5.3	445	1 x 1/2"	42½ x 31½ x 31
M17	60	35	Honda GX630	17.4	3300	2400	5.3	450	1 x 1/2"	42½ x 31½ x 31

*Length includes tow bar

Sound level maximum is 82 db(A) at 23 feet.


Outstanding Advantages

- Contemporary, compact design, fits easily in the back of a pickup truck
- Single stage, oil injected rotary screw airend with power-saving proprietary Sigma Profile[™]
- · Heavy-duty Honda engine
- · Large 5 gallon fuel tank for extended run-time
- · Extremely low sound level
- · Easy access and serviceability
- · Protective rotomolded polyethylene enclosure
- · Lightweight and easy to maneuver
- Available as stationary mount

Optional 5 Year Warranty

To protect your investment, all of our Mobilair compressors are available with an optional 5 year warranty on the compressor airend.

		KAESER COMPRESSORS Built for a Medius					
Warranty		Optional Five Year Mobilair ¹¹¹ Portable Compressor					
non	Seld No.	Bartup Dete					
For expanding the control to factor, it the odd David any factor is control to factor any other than factor approach the david property of the factor approach is the patient effect to react any factor of approach is the patient effect to react any other and approach is the patient effect to react any other any approach is the patient effect to react any reaction of approach is the patient effect to react any reaction of a sector of the patient of the transmission reaction of a sector of the patient of the transmission reaction of approach is built to the patient of the transmission reaction of the patient of the patient of the transmission reaction of the patient of the patient of the transmission of the patient of the patient of the patient of the transmission of the patient of the patient of the patient of the transmission of the patient of the patient of the patient of the transmission of the patient of the patient of the patient of the transmission of the patient of the patient of the patient of the patient of the transmission of the patient of the patient of the patient of the transmission of the patient of the patient of the patient o	t new design of the second period of the second of period of the second of the second of the second of the second of the second of the second						
No. and the second is a second of the full second							
> factor's milital except policy, and provident priceway vertability falses, profile for state fault straige app, to identify versely prival							
 If second sector before the teacher of the an address flaten across here; 							
 Entering mark and allebed installed separated late, alleb 10 late, if anyword protein. 							
 Exercise text publics as pread markening to get use of the text of the objected variable. The Electricity conditions patient has required for plantice serving 1 different air sex. Additional parts and had ing for regional ingenetial even than 1 different air yea. 							
 Summer and blic dipension more reported a solid burning and which are poor explorer all should have been building second. 							
namediated, hydrologicon, debut a setting a - (het Yame'), itsehel islam; point a Te grade is i	rationet brothed have	In the product products factory to the definition and perchantics ended to any sector and the constitution and an electric definition of the definition factor of the sector and the sector and the sector and the sector and the sector and the sec- tor the definition. The Court is the sector and an and the sector and the sec- tor the definition of the sector and the sector and the sector and the sec-					







Built for a lifetime."

Kaeser Compressors, Inc. 511 Sigma Drive Fredericksburg, VA 22408 USA Telephone: 540-898-5500 Toll Free: 800-777-7873 info.usa@kaeser.com



Kaeser Compressors Canada Inc. 3760 La Verendrye Street Boisbriand, QC J7H 1R5 CANADA Telephone: (450) 971-1414 Toll free: (800) 477-1416 info.canada@kaeser.com

Kaeser Compresores de México S de RL de CV Calle 2 #123 Parque Industrial Juríca

76100 Querétaro, Qro.

Telephone: 01 (442) 218 64 48

sales.mexico@kaeser.com

Kaeser Compresores de Guatemala y Cia. Ltda. Calz. Atanasio Tzul 21-00, zona 12 El Cortijo II, Bodega 501 01012–Guatemala City Telephone: +502 2412-6000 info.guatemala@kaeser.com

www.kaeser.com



© 2016 Kaeser Compressors, Inc. All rights reserved. 10/16 USM15M17

Specifications are subject to change without notice.